



Typhoon 8,3m



Description

The PTO mixers Typhoon are the robust ones with solid construction of frame, for open slurry pits and slurry lagoons. There are three different versions for selection: the standard version, the reinforced version the extra strong version. All Typhoon mixer are with long lasting ball bearing free special mounting of the drive shaft in the aggressive slurry - insensitive to leftovers, straw and animal hair.

At a glance

- There are 3 different types.
- Completely galvanized.
- Special wooden bearings in the aggressive slurry.
- Length of mixer: 4,4 - 9,3 m.

Applications

- For open slurry pits and slurry lagoons.

Versions

Standard version

For tractors with up to about 100 HP
 Mixer tube 101 mm Ø
 Mixer shaft 35 mm Ø
 Completely galvanized (Propeller painted)
 Incl. high efficiency propeller TR-PH 500 (500 mm Ø)
 Length of mixer: 4,4 m – 7,4 m

Strong version

For tractors with more than about 100 HP
 Mixer tube 140 mm Ø
 Mixer shaft 35 mm Ø
 Completely galvanized (Propeller painted)
 Incl. high efficiency propeller TR-PH 500 (500 mm Ø)
Reinforced three-point jack
Specially reinforced mounting
 Length of mixer: 6,3 m – 8,3 m

Extra strong version

For tractors with more than about 100 HP
 Mixer tube 140 mm Ø
 Mixer shaft 45 mm Ø
 Completely galvanized (Propeller painted)
 Incl. high efficiency propeller TR-PH 600 (600 mm Ø)*
Reinforced three-point jack
Specially reinforced mounting
 Length of mixer: 6,3 m – 9,3 m

Media



Accessories

Accessories



Propeller stay long



Propeller protection ring
To protect the high efficiency propeller



Propeller protection ring with tyre fixation
Propeller protection ring with tyre fixation for plastic lined lagoons (without tyre)



High efficiency shredder with counter blade



OCELOT - Frame Extension
With the Ocelot frame extension you can mix slurry towers up to 3 m above the ground level.



Reverse transmission



Reinforced bearing unit for standard mixing rod.



Cardan shaft
Cardan shaft required.