



Description

The Typhoon more is the optimal PTO mixer for big slurry pits and lagoons. There are mixer length until 11,3m available.
 In order to stabilize the mixer tube, the PTO mixer Typhoon more is reinforced with a welded on triangle mast. Instead of dirt- sensible rolling bearings with seals which do rarely withstand the aggressive slurry for a long time (for example animal hairs) the Reck slurry mixers are equipped with the extremely resistant special slide bearings. They are long living, maintenance friendly and have proved very well over decades in the slurry sector.

At a glance

- Extra strong version.
- Completely galvanized.
- Long lasting, ball bearing free special slide bearing
- Length of mixer 9,3 m - 11,3 m.

Applications

- For open slurry pits and slurry lagoons

Versions

Extra strong version

For tractors with more than about 100 HP

Mixer tube 140 mm \varnothing

Mixer shaft 45 mm \varnothing

Completely galvanized (Propeller painted)

Incl. high efficiency Propeller TR-PH 600 (600 mm \varnothing)

Reinforced three-point jack

Specially reinforced mounting

With welded on triangle stabilizer

Length of mixer: 9,3 m - 11,3 m

Media



Accessories

Accessories



Propeller stay long



Propeller protection ring
To protect the high efficiency propeller



Propeller protection ring with tyre fixation
Propeller protection ring with tyre fixation for plastic lined lagoons (without tyre)



Reverse transmission



High efficiency shredder with counter blade



Cardan shaft
Cardan shaft required.